

# 14" PCAP Touch Monitor



## Features

- PCAP multi-touch
- Plastic frame, rugged steel housing
- Convex full flat fillet design
- High reliability testing, stable performance
- Anti-glare surface
- **Application**  
Non-cash equipment / VTM / ATM / Kiosk etc

## Ordering Information

USMP-F140-192108CBZ-A0	IP with 14" LCD, 250nits(optional), 1920x1080 pixels, 170(H)x170(V), LED Backlight, 30ms(Typ. Tr+Tf);
	VGA/DVI-D/USB, <b>PCAP Touch(10 points)</b> ;

## Specifications

### LCD

Model Name	USMP-F140-192108CBZ-A0
Screen Size	14"
Active Display Area(mm)	309.312(H)x173.988(V)
Pixel Pitch(mm)	0.264(H)x0.264(V)
Display Mode	Normally white
Display Color	262K
Display Resolution(pixel)	1920x1080
Contrast Ratio	800:1
Brightness	250nits
Backlight	LED
Viewing Angles(CR=10)	170(H);170(V)
Response Time(Typ. Tr+Tf)	30ms

### Optional

Touch Screen	PCAP Touch(10 points)
Electromagnetic pen	Optional

### I/O Interface

Signal Connector	VGA/DVI-D
Power Consumption	DC 12V
Touch Controller	USB

### Mechanical

Dimension(VxHxT)mm	339x212x33
--------------------	------------

### Environmental

Operating Temperature	0~50°C(not clotted)
Storage Temperature	-20~60°C(not clotted)
Relative Humidity	5~90(%RH)