



US Micro Products
Electronic Products for the OEM

OLED PRODUCT SPECIFICATION

Manufactured by:



PART NUMBER:	USMP-P18701
DESCRIPTION:	0.7" OLED, White, 96x16 Resolution, COG, SSD 1307

ISSUE DATE	APPROVED BY (Customer Use Only)	CHECKED BY	PREPARED BY
PROPRIETARY NOTE:	THIS SPECIFICATION IS THE PROPERTY OF US MICRO PRODUCTS AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF US MICRO PRODUCTS AND MUST BE RETURNED TO US MICRO PRODUCTS UPON ITS REQUEST.		

REVISION RECORD

REV.	REVISION DESCRIPTION	REV. DATE	REMARK
X01	INITIAL RELEASE	2007. 09. 07	
X02	<ul style="list-style-type: none"> ■ Add the information of module weight ■ Modify luminance & lifetime specifications ■ Modify D.C electrical characteristics ■ Modify panel electrical specifications ■ Add graphic display data ram address map ■ Add power on/off sequence ■ Add application circuit ■ Modify polarizer dimension 	2007. 10. 31	Page 5, 6, 7, 8, 11, 12, 14, 15 & 17
A01	<ul style="list-style-type: none"> ■ Transfer from X version ■ Modify D.C electrical characteristics ■ Modify power on/off sequence ■ Add packing specification 	2008. 04. 08	Page 7, 14 & 18
A02	<ul style="list-style-type: none"> ■ Modify product name - RGC07096016WR000→ RGS07096016WR000 	2008. 05. 27	Page 1

CONFIDENTIAL

CONTENTS

ITEM	PAGE
1. SCOPE	4
2. WARRANTY	4
3. FEATURES	4
4. MECHANICAL DATA	5
5. MAXIMUM RATINGS	6
6. ELECTRICAL CHARACTERISTICS	7
6.1 D.C ELECTRICAL CHARACTERISTICS	
6.2 ELECTRO-OPTICAL CHARACTERISTICS	
7. INTERFACE	9
7.1 FUNCTION BLOCK DIAGRAM	
7.2 PANEL LAYOUT DIAGRAM	
7.3 PIN ASSIGNMENTS	
7.4 GRAPHIC DISPLAY DATA RAM ADDRESS MAP	
7.5 INTERFACE TIMING CHART	
8. POWER ON / OFF SEQUENCE & APPLICATION CIRCUIT	14
8.1 POWER ON / OFF SEQUENCE	
8.2 APPLICATION CIRCUIT	
8.3 COMMAND TABLE	
9. RELIABILITY TEST CONDITIONS	16
10. EXTERNAL DIMENSION	17
11. PACKING SPECIFICATION	18
12. APPENDIXES	19

CONFIDENTIAL

1. SCOPE

The purpose of this specification is to define the general provisions and quality requirements that apply to the supply of display cells manufactured by RiTdisplay. This document, together with the Module Assembly Drawing, is the highest-level specification for this product. It describes the product, identifies supporting documents and contains specifications, which are either not addressed, or are exceptions to the supporting documents.

2. WARRANTY

RiTdisplay warrants that the products delivered pursuant to this specification (or order) will conform to the agreed specifications for twelve (12) months from the shipping date ("Warranty Period"). RiTdisplay is obligated to repair or replace the products which are found to be defective or inconsistent with the specifications during the Warranty Period without charge, on condition that the products are stored or used as the conditions specified in the specifications. Nevertheless, RiTdisplay is not obligated to repair or replace the products without charge if the defects or inconsistency are caused by the force majeure or the reckless behaviors of the customer.

After the Warranty Period, all repairs or replacements of the products are subject to charge.

3. FEATURES

- Small molecular organic light emitting diode.
- Color : White
- Panel matrix : 96*16
- Driver IC : SSD1307
- Excellent Quick response time : 10 μ s
- Extremely thin thickness for best mechanism design : 1.41 mm
- High contrast : 2000:1
- Wide viewing angle : 160°
- I²C Interface
- Strong environmental resistance
- Wide range of operating temperature : -40 to 70°C
- Anti-glare polarizer.

4. MECHANICAL DATA

NO	ITEM	SPECIFICATION	UNIT
1	Dot Matrix	96 (W) x 16 (H)	dot
2	Dot Size	0.164 (W) x 0.185 (H)	mm ²
3	Dot Pitch	0.184 (W) x 0.205 (H)	mm ²
4	Aperture Rate	80	%
5	Active Area	17.644 (W) x 3.26 (H)	mm ²
6	Panel Size	26.3 (W) x 8 (H)	mm ²
7	Panel Thickness	1.41 ± 0.1	mm
8	Module Size	46.3 (W) x 8 (H) x 1.41 (D)	mm ³
9	Diagonal A/A size	0.7	inch
10	Module Weight	0.62 ± 10%	gram

CONFIDENTIAL

5. MAXIMUM RATINGS

ITEM	MIN	MAX	UNIT	Condition	Remark
Supply Voltage (V_{DD})	-0.3	+4	V	Ta = 25 °C	IC maximum rating
Supply Voltage (V_{CC})	7	16	V	Ta = 25 °C	IC maximum rating
Operating Temp.	-40	70	°C		
Storage Temp	-40	85	°C		
Humidity		85	%		
Life Time	18,000	-	Hrs	160 cd/m ² , 50% checkerboard	Note (1)
Life Time	21,000	-	Hrs	140 cd/m ² , 50% checkerboard	Note (2)
Life Time	25,000	-	Hrs	120 cd/m ² , 50% checkerboard	Note (3)

Note:

(A) Under VCC = 10V, Ta = 25°C, 50% RH.

(B) Life time is defined the amount of time when the luminance has decayed to less than 50% of the initial measured luminance.

(1) Setting of 160 cd/m² :

- Contrast setting : 0x41H
- Frame rate : 105Hz
- Duty setting : 1/16

(2) Setting of 140 cd/m² :

- Contrast setting : 0x39H
- Frame rate : 105Hz
- Duty setting : 1/16

(3) Setting of 120 cd/m² :

- Contrast setting : 0x31H
- Frame rate : 105Hz
- Duty setting : 1/16

6. ELECTRICAL CHARACTERISTICS

6.1 D.C ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETERS	TEST CONDITION	MIN	TYP	MAX	UNIT
V_{CC}	Analog power supply (for OLED panel)	$T_a = -20\text{ }^{\circ}\text{C}$ to $+70\text{ }^{\circ}\text{C}$	9.5	10	10.5	V
V_{DD}	Digital power supply	$T_a = -20\text{ }^{\circ}\text{C}$ to $+70\text{ }^{\circ}\text{C}$	1.65	2.8	3.3	V
I_{DD}	Operating current for V_{DD} $V_{DD} = 2.8\text{V}$, $V_{CC} = 12\text{V}$, $I_{REF} = 10\text{uA}$ No Panel attached, All Display ON	Contrast=FF	-	23	30	μA
I_{CC}	Operating current for V_{CC} $V_{DD} = 2.8\text{V}$, $V_{CC} = 12\text{V}$, $I_{REF} = 10\text{uA}$ No panel attached, All Display ON	Contrast=FF	-	455	590	μA
V_{IH}	High logic input level		$0.8 * V_{DD}$	-	-	V
V_{IL}	Low logic input level		-	-	$0.2 * V_{DD}$	V
V_{OH}	High logic output level	$I_{OUT} = 100\text{uA}$, 3.3MHz	$0.9 * V_{DD}$	-	-	V
V_{OL}	Low logic output level	$I_{OUT} = 100\text{uA}$, 3.3MHz	-	-	$0.1 * V_{DD}$	V
I_{SEG}	Segment on output current $V_{DD} = 2.8\text{V}$, $V_{CC} = 12\text{V}$, $I_{REF} = 10\text{uA}$, Display on,	Contrast=FF	285	316	345	μA
		Contrast=AF	-	217	-	μA
		Contrast=7F	-	158	-	μA
		Contrast=3F	-	79	-	μA
		Contrast=0F	-	19	-	μA

Note : The V_{CC} input must keep in a stable value; ripple and noise are not allowed.

6.2 ELECTRO-OPTICAL CHARACTERISTICS

PANEL ELECTRICAL SPECIFICATIONS

PARAMETER	MIN	TYP.	MAX	UNITS	COMMENTS
Normal mode current		3	5	mA	All pixels on (1)
Standby mode current		0.4	0.6	mA	Standby mode 10% pixels on (2)
Normal mode power consumption		30	50	mW	All pixels on (1)
Standby mode power consumption		4	6	mW	Standby mode 10% pixels on (2)
Normal mode Luminance	120	140		cd/m ²	Display Average
Standby mode Luminance		20		cd/m ²	
CIE _x (White)	0.24	0.28	0.32		x, y (CIE 1931)
CIE _y (White)	0.28	0.32	0.36		
Dark Room Contrast	2000:1				
Viewing Angle	160			degree	
Response Time		10		μs	

(1) Normal mode condition :


- Driving Voltage : 10V
- Contrast setting : 0x39H
- Frame rate : 105Hz
- Duty setting : 1/16

(2) Standby mode condition :


- Driving Voltage : 10V
- Contrast setting : 0x05H
- Frame rate : 105Hz
- Duty setting : 1/16

7. INTERFACE

7.1 FUNCTION BLOCK DIAGRAM



7.2 PANEL LAYOUT DIAGRAM



CONFIDENTIAL

7.3 PIN ASSIGNMENTS

Pin No.	Pin Name	Description
1	VSS	This is a ground pin.
2	RES#	Hardware reset signal
3	SCL(D0)	I ² C serial clock pin
4	SDA(D2,D1)	I ² C serial data pin
5	IREF	The current reference input pin, this pin should be connected to ground through a resistor.
6	VCOMH	The COM voltage reference pin, this pin should be connected to ground through a capacitor.
7	VCC	Positive OLED high voltage power supply
8	VDD	Power supply for logic circuit

CONFIDENTIAL

7.4 GRAPHIC DISPLAY DATA RAM ADDRESS MAP

The GDDRAM is a bit mapped static RAM holding the bit pattern to be displayed. The size of the RAM is 128 x 39 bits and the RAM is divided into five pages, from PAGE0 to PAGE4, which are used for monochrome 128x39 dot matrix display, as shown in below figures.

When one data byte is written into GDDRAM, all the rows image data of the same page of the current column are filled (i.e. the whole column (8 bits) pointed by the column address pointer is filled.). Data bit D0 is written into the top row, while data bit D7 is written into bottom row. For PAGE4, bit D7 is treated as don't care bit.

For mechanical flexibility, re-mapping on both Segment and Common outputs can be selected by software. For vertical shifting of the display, an internal register storing the display start line can be set to control the portion of the RAM data to be mapped to the display (command D3h).

CONFIDENTIAL

GDDRAM pages structure of SSD1307

Segment re-mapping (command A1h)		SEG127	SEG126	SEG125	SEG124	SEG4	SEG3	SEG2	SEG1	SEG0			
Segment re-mapping (command A0h [RESET])		SEG0	SEG1	SEG2	SEG3	SEG123	SEG124	SEG125	SEG126	SEG127			
Page	Data	COL0	COL1	COL2	COL3	COL123	COL124	COL125	COL126	COL127	COM Output Scan Direction (command C0h [RESET])	COM Output Scan Direction (command C8h)	
0	D0										COM0	COM38	
	D1												COM1	COM37
	D2												COM2	COM36
	D3												COM3	COM35
	D4												COM4	COM34
	D5												COM5	COM33
	D6												COM6	COM32
	D7												COM7	COM31
1	D0										COM8	COM30	
	D1												COM9	COM29
	D2												COM10	COM28
	D3												COM11	COM27
	D4												COM12	COM26
	D5												COM13	COM25
	D6												COM14	COM24
	D7												COM15	COM23
2	D0										COM16	COM22	
	D1												COM17	COM21
	D2												COM18	COM20
	D3												COM19	COM19
	D4												COM20	COM18
	D5												COM21	COM17
	D6												COM22	COM16
	D7												COM23	COM15
3	D0										COM24	COM14	
	D1												COM25	COM13
	D2												COM26	COM12
	D3												COM27	COM11
	D4												COM28	COM10
	D5												COM29	COM9
	D6												COM30	COM8
	D7												COM31	COM7
4	D0										COM32	COM6	
	D1												COM33	COM5
	D2												COM34	COM4
	D3												COM35	COM3
	D4												COM36	COM2
	D5												COM37	COM1
	D6												COM38	COM0
D7	Don't care bit													


Each box represents one bit of image data

CONFIDENTIAL

7.5 INTERFACE TIMING CHART

I²C Interface Timing Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
t_{cycle}	Clock Cycle Time	2.5	-	-	us
t_{HSTART}	Start condition Hold Time	0.6	-	-	us
t_{HD}	Data Hold Time (for "SDA _{OUT} " pin)	0	-	-	ns
	Data Hold Time (for "SDA _{IN} " pin)	300	-	-	ns
t_{SD}	Data Setup Time	100	-	-	ns
t_{SSTART}	Start condition Setup Time (Only relevant for a repeated Start condition)	0.6	-	-	us
t_{SSTOP}	Stop condition Setup Time	0.6	-	-	us
t_{R}	Rise Time for data and clock pin	-	-	300	ns
t_{F}	Fall Time for data and clock pin	-	-	300	ns
t_{IDLE}	Idle Time before a new transmission can start	1.3	-	-	us




8. POWER ON / OFF SEQUENCE & APPLICATION CIRCUIT

8.1 POWER ON / OFF SEQUENCE

Power ON sequence:

1. Power ON V_{DD}
2. After V_{DD} become stable, set RES# pin LOW (logic low) for at least 3us (t_1)⁽³⁾ and then HIGH (logic high).
3. After set RES# pin LOW (logic low), wait for at least 3us (t_2). Then Power ON V_{CC} .⁽¹⁾
4. After V_{CC} become stable, send command AFh for display ON. SEG/COM will be ON after 100ms (t_{AF}).


The Power ON sequence



Power OFF sequence:

1. Send command AEh for display OFF.
2. Power OFF V_{CC} ^{(1), (2)}
3. Power OFF V_{DD} after t_{OFF} .⁽⁴⁾ (where Minimum t_{OFF} =80ms, Typical t_{OFF} =100ms)


The Power OFF sequence



Note:

- ⁽¹⁾ V_{CC} should be disabled when it is OFF.
- ⁽²⁾ Power Pins (V_{DD} , V_{CC}) can never be pulled to ground under any circumstance.
- ⁽³⁾ The register values are reset after t_1 .
- ⁽⁴⁾ V_{DD} should not be Power OFF before V_{CC} Power OFF.

8.2 APPLICATION CIRCUIT



Component:

C1, C2: 4.7uF/16V(0805)

C3: 0.1uF/16V(0603)

R1: 3M ohm 1% (0603)

R2, R3: 10K ohm(0603)

This circuit is for I²C interface.

8.3 COMMAND TABLE

Refer to SSD1307 IC Spec.

9. RELIABILITY TEST CONDITIONS

No.	Items	Specification	Quantity
1	High temp. (Non-operation)	85°C, 240hrs	5
2	High temp. (Operation)	70°C, 120hrs	5
3	Low temp. (Operation)	-40°C, 120hrs	5
4	High temp. / High humidity (Operation)	65°C, 90%RH, 120hrs	5
5	Thermal shock (Non-operation)	-40°C ~85°C (-40°C /30min; transit /3min; 85°C /30min; transit /3min) 1cycle: 66min, 100 cycles	5
6	Vibration	Frequency : 5~50HZ, 0.5G Scan rate : 1 oct/min Time : 2 hrs/axis Test axis : X, Y, Z	1 Carton
7	Drop	Height: 120cm Sequence : 1 angle 、 3 edges and 6 faces Cycles: 1	1 Carton
8	ESD (Non-operation)	Air discharge model, ±8kV, 10 times	5


Test and measurement conditions

1. All measurements shall not be started until the specimens attain to temperature stability.
2. All-pixels-on is used as operation test pattern.
3. The degradation of Polarizer are ignored for item 1, 4 & 5.

Evaluation criteria

1. The function test is OK.
2. No observable defects.
3. Luminance: > 50% of initial value.
4. Current consumption: within ± 50% of initial value.


10. EXTERNAL DIMENSION



CONFIDENTIAL

11. PACKING SPECIFICATION

CONFIDENTIAL



This document contains confidential and proprietary information. Neither it nor the information contained herein shall be disclosed to others or duplicated or used for others without the express written consent of RiTdisplay.

12. APPENDIXES

APPENDIX 1: DEFINITIONS

A. DEFINITION OF CHROMATICITY COORDINATE

The chromaticity coordinate is defined as the coordinate value on the CIE 1931 color chart for R, G, B, W.

B. DEFINITION OF CONTRAST RATIO

The contrast ratio is defined as the following formula:

$$\text{Contrast Ratio} = \frac{\text{Luminance of all pixels on measurement}}{\text{Luminance of all pixels off measurement}}$$

C. DEFINITION OF RESPONSE TIME

The definition of turn-on response time T_r is the time interval between a pixel reaching 10% of steady state luminance and 90% of steady state luminance. The definition of turn-off response time T_f is the time interval between a pixel reaching 90% of steady state luminance and 10% of steady state luminance. It is shown in Figure 2.




Figure 2 Response time

D. DEFINITION OF VIEWING ANGLE

The viewing angle is defined as Figure 3. Horizontal and vertical (H & V) angles are determined for viewing directions where luminance varies by 50% of the perpendicular value.





Figure 3 Viewing Angle

APPENDIX 2: MEASUREMENT APPARATUS


A. LUMINANCE/COLOR COORDINATE

PHOTO RESEARCH PR-705, MINOLTA CS-100




B. CONTRAST / RESPONSE TIME / VIEWING ANGLE

WESTAR CORPORATION FPM-510



CONFIDENTIAL

C. ESD ON AIR DISCHARGE MODE



CONFIDENTIAL

APPENDIX 3: PRECAUTIONS**A. RESIDUE IMAGE**

Because the pixels are lighted in different time, the luminance of active pixels may reduce or differ from inactive pixels. Therefore, the residue image will occur. To avoid the residue image, every pixel needs to be lighted up uniformly.

CONFIDENTIAL



Displays

US Micro Products is an industrial distributor specializing in engineered display solutions. We dedicate ourselves to providing the best in displays for the medical, industrial, gaming, automotive, aerospace, military and consumer markets.

OLEDs



TFT Display



Open Frame Monitors



Passive LCDs



Multitouch



Touch Screen



As our customer, you receive expert knowledge, support and service. Our technical sales staff and experienced design engineers provide answers to your questions and engineered solutions to meet your display needs.

Peripheral Devices

Our full line of peripheral devices includes keyboards, trackballs and printers. These rugged industrial products are designed to meet the rigorous demands of your equipment and are available in a variety of standard and custom options.

Keyboards



Trackballs



Aerospace Trackballs



Printers

