

## PRODUCT DATASHEET

## **SPECIFICATIONS**

Part Number USMP-A058-112243UGB-A0  Diagonal Size (inch) 5.8  Shape Rectangle  Resolution 1125 x 2436  Outline Dimension (mm) 67.63(H) x 143.12(V) x 0.5(D)  Active Area (mm) 62.33(H) x 134.95(V)  Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70  Storage Temperature (°C) -40 ~ 85		
Shape Resolution 1125 x 2436  Outline Dimension (mm) 67.63(H) x 143.12(V) x 0.5(D)  Active Area (mm) 62.33(H) x 134.95(V)  Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Part Number	USMP-A058-112243UGB-A0
Resolution 1125 x 2436  Outline Dimension (mm) 67.63(H) x 143.12(V) x 0.5(D)  Active Area (mm) 62.33(H) x 134.95(V)  Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Diagonal Size (inch)	5.8
Outline Dimension (mm) 67.63(H) x 143.12(V) x 0.5(D)  Active Area (mm) 62.33(H) x 134.95(V)  Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Shape	Rectangle
Active Area (mm) 62.33(H) x 134.95(V)  Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Resolution	1125 x 2436
Interface 4-Lane MIPI(AMOLED)/I2C(CTP)  Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Outline Dimension (mm)	67.63(H) x 143.12(V) x 0.5(D)
Brightness (cd/m²) 450  Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Active Area (mm)	62.33(H) x 134.95(V)
Contrast Ratio 60000  Viewing Angle 80/80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Interface	4-Lane MIPI(AMOLED)/I2C(CTP)
Viewing Angle 80/80/80  Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Brightness (cd/m²)	450
Touch Screen CTP  Operating Temperature (°C) -20 ~ 70	Contrast Ratio	60000
Operating Temperature (°C) -20 ~ 70	Viewing Angle	80/80/80/80
	Touch Screen	CTP
Storage Temperature (°C) -40 ~ 85	Operating Temperature (°C)	-20 ~ 70
	Storage Temperature (°C)	-40 ~ 85

## **APPLICATIONS**

- Gaming
- Consumer
- Smart Home

## **FEATURES**

- Wide Viewing Angle
- High-Resolution Clarity
- · Superior Contrast Ratio
- RoHS Compliant

PROPRIETARY NOTE: THIS DATASHEET IS THE PROPERTY OF US MICRO PRODUCTS AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF US MICRO PRODUCTS AND MUST BE RETURNED TO US MICRO PRODUCTS UPON ITS REQUEST.

(800) 741-7755

www.usmicroproducts.com