

15"PCAP Touch Monitor



Features

- Full Flat Surface
- PCAP Multi-touch
- Plastic frame, rugged steel housing
- Wide Temperature
- Electromagnetic Pen/Privacy Film optional
- **Application:**
ATM / Kiosk / Non-cash Equipment etc

Ordering Information

USMP-F150-102076CBZ-A0	OP with 15" LCD,300nits(optional),700:1,1024x768 pixel,160(H)x140(V),LED Backlight, 8ms (Typ.Tr+Tf); VGA/DVI-D/USB,PCAP Touch(10 points);
-------------------------------	---

Specifications

LCD

Model Name	USMP-F150-102076CBZ-A0
Screen Size	15"
Active Display Area(mm)	304.128(H)x228.096(V)
Pixel Pitch(mm)	0.297(H)x0.297(V)
Display Mode	Normally white
Display Resolution(pixel)	1024x768
Contrast Ratio	700:1
Brightness	250/350/450nits
Backlight	LED
Viewing Angles(CR=10)	160(H);140(V)
Response Time(Typ.Tr+Tf)	8ms

Optional

Touch Screen	PCAP Touch(10 points)
Electromagnetic Pen	Optional
Privacy Film	Optional

I/O Interface

Signal Connector	VGA/DVI-D/USB
Power Consumption	DC 12V
Touch Controller	USB

Mechanical

Dimension(VxHxT)mm	349.8x273.8x41.9
--------------------	------------------

Environmental

Operating Temperature	-20~70°C(not clotted)
Storage Temperature	-30~80°C(not clotted)
Relative Humidity	5~90(%RH)