

21.5" PCAP Touch Monitor



Features

- Full Flat Surface
- PCAP touchscreen(10 points)
- Plastic frame, rugged steel housing
- Great heat dissipation
- Water proof IP65/ oil resistant
- High Reliability and longtime

- **Application:**

VTM / Kiosk / Non-cash Equipment etc

Ordering Information

USMP-F215-192108CBZ-B0	OP with 21.5" LCD,250nits(optional),1920x1080 pixels,178(H)x178(V),LED Backlight,18ms(Typ.Tr+Tf);
	3000:1,VGA/DVI-D/USB,PCAP Touch(10 points);

Specifications

LCD

Model Name	USMP-F215-192108CBZ-B0
Screen Size	21.5"
Active Display Area(mm)	476.64(H)x268.116(V)
Pixel Pitch(mm)	0.24825(H)x0.24825(V)
Display Mode	Normally Black
Display Resolution(pixel)	1920x1080
Contrast Ratio	3000:1
Brightness	250nits
Backlight	LED
Viewing Angles(CR=10)	178(H);178(V)
Response Time(Typ.Tr+Tf)	18ms

Optional

Touch Screen	PCAP Touch(10 points)
Electromagnetic pen	Optional
Privacy Film	Optional

I/O Interface

Signal Connector	VGA/DVI-D
Power Consumption	DC 12V
Touch Controller	USB

Mechanical

Dimension(VxHxT)mm	518x313.9x45.5
--------------------	----------------

Environmental

Operating Temperature	0~50°C(not clotted)
Storage Temperature	-20~60°C(not clotted)
Relative Humidity	5~90(%RH)