

21.5" PCAP Touch Monitor



Features

- PCAP Multi-touch
- Full flat surface
- White aluminum front frame / touch screen cover
- Anti-glare LCD surface treatment
- Surface IP65 waterproof, dustproof, vandal-proof
- **Application:**
Medical self-service equipment / Kiosk etc

Ordering Information

USMP-F215-192108CBZ-C0	OP with 21.5" LCD,250nits,3000:1,1920x1080 pixel,178(H)x178(V),LED Backlight,
	18ms(Typ.Tr+Tf);VGA/DVI/HDMI/USB/Audio, PCAP Touch(10 points) ;

Specifications

LCD

Model Name	USMP-F215-192108CBZ-C0
Screen Size	21.5"
Active Display Area(mm)	476.064(H)x267.786(V)
Pixel Pitch(mm)	0.24795(H)x0.24795(V)
Display Mode	Normally black
Display Resolution(pixel)	1920x1080
Contrast Ratio	3000:1
Display Color	16.7M
Brightness	250/350/450nits
Backlight	LED
Viewing Angles(CR=10)	178(H);178(V)
Response Time(Typ.Tr+Tf)	18ms

Optional

Touch Screen	PCAP Touch(10 points)
Tempered glass	Optional

I/O Interface

Signal Connector	VGA /DVI-D/HDMI/Audio
Power Consumption	DC 12V
Touch Controller(Optional)	USB

Mechanical

Dimension(VxHxT)mm	511.9x303.4x43
--------------------	----------------

Environmental

Operating Temperature	0~50°C(not clotted)
Storage Temperature	-20~60°C(not clotted)
Relative Humidity	5~90(%RH)