

# TFT SPECIFICATION

|                 |                     |
|-----------------|---------------------|
| Part Number     | USMP-TT043WS-01F    |
| Size            | 4.3"                |
| Resolution      | 480 * 3 (RGB) * 272 |
| Brightness      | 460                 |
| Contrast        | 600                 |
| Viewing Angle   | 60/60/60/60         |
| Operating Temp. | -20c to 70c         |

## TFT Benefits:

- Great durability
- Multiple customizations
- Wide variety of sizes
- Long lifetime

FOR ADDITIONAL INFORMATION  
PLEASE CONTACT:

[engineering@usmicroproducts.com](mailto:engineering@usmicroproducts.com)

| Issue Date | Approved by (customer use) | Checked by | Prepared by |
|------------|----------------------------|------------|-------------|
|            |                            |            |             |

PROPRIETARY NOTE: THIS SPECIFICATION IS THE PROPERTY OF US MICRO PRODUCTS AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF US MICRO PRODUCTS AND MUST BE RETURNED TO US MICRO PRODUCTS UPON ITS REQUEST.

**(800) 741-7755**  
[www.usmicroproducts.com](http://www.usmicroproducts.com)

## History of Version

| Date<br>(mm / dd / yyyy) | Ver. | Edi. | Description  | Page               | Design by |
|--------------------------|------|------|--|--------------------|-----------|
| 05/22/2014               | 01   | 001  | New Drawing.   | -                  | Howard    |
| 06/04/2014               | 01   | 002  | Second Drawing<br>Disp pin internal connect to H<br>Modify Frame Drawing | 12<br>Appendix     | Howard    |
| 07/15/2014               | 01   | 003  | New Sample   | -                  | Howard    |
| 05/26/2015               | 01   | 004  | Modify Average Brightness<br>Add LED Life Time<br>Add Rear View          | 6<br>9<br>Appendix | Howard    |
| 10/20/2015               | 01   | 005  | Modify Packaging Specification   | Appendix           | Howard    |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |
|                          |      |      |  |                    |           |

Total: 27 Pages

## Contents

### 1. SPECIFICATIONS

- 1.1 Features
- 1.2 Mechanical Specifications
- 1.3 Absolute Maximum Ratings
- 1.4 DC Electrical Characteristics
- 1.5 Optical Characteristics
- 1.6 Backlight Characteristics

### 2. MODULE STRUCTURE

- 2.1 Counter Drawing
- 2.2 Interface Pin Description
- 2.3 Timing Characteristics

### 3. QUALITY ASSURANCE SYSTEM

- 3.1 Quality Assurance Flow Chart
- 3.2 Inspection Specification

### 4. RELIABILITY TEST

- 4.1 Reliability Test Condition

### 5. PRECAUTION RELATING PRODUCT HANDLING

- 5.1 Safety
- 5.2 Handling
- 5.3 Storage
- 5.4 Terms of Warranty

Appendix : 1. LCM Drawing

2. Packaging Specification

Note : For detailed information please refer to IC data sheet :

Primacy(TFT LCD): Sitronix--ST7282-G4

(Or compatible IC )

## 1. SPECIFICATIONS

### 1.1 Features

| Item                        | Standard Value  |
|-----------------------------|---|
| Display Type                | 480 * 3 (RGB) * 272 Dots  |
| LCD Type                    | a-Si TFT , Normally white, Transmissive type  |
| Screen size(inch)           | 4.3 inch  |
| Viewing Direction           | 6 O'clock   |
| Color configuration         | RGB-Strip   |
| Backlight Type              | LED B/L   |
| Interface                   | Digital 24-bits RGB   |
| Other(controller/driver IC) | ST7282-G4<br>(Or Compatible IC )  |
| ROHS                        | THIS PRODUCT CONFORMS THE ROHS OF PTC<br>Detail information please refer website :<br><a href="http://www.powertip.com.tw/news.php?area_id_view=1085560481/">http://www.powertip.com.tw/news.php?area_id_view=1085560481/</a> |

### 1.2 Mechanical Specifications

| Item              | Standard Value                       | Unit |
|-------------------|--------------------------------------|------|
| Outline Dimension | 105.5(W) x 67.2 (L) x 2.6(H) +0,-0.2 | mm   |

#### LCD panel

| Item         | Standard Value         | Unit |
|--------------|------------------------|------|
| Viewing Area | 96.7 (W) * 55.3 (L)    | mm   |
| Active Area  | 95.04 (W) x 53.856 (L) | mm   |
| Pixel Size   | 0.198 (W) * 0.198 (H)  | mm   |

Note : For detailed information please refer to LCM drawing

### 1.3 Absolute Maximum Ratings

#### Module

| Item                        | Symbol          | Condition  | Min. | Max. | Unit |
|-----------------------------|-----------------|------------|------|------|------|
| System Power Supply Voltage | VDD             | GND=0      | -0.3 | 4.6  | V    |
| Operating Temperature       | T <sub>OP</sub> | -          | -20  | 70   | °C   |
| Storage Temperature         | T <sub>ST</sub> | -          | -30  | 80   | °C   |
| Storage Humidity            | H <sub>D</sub>  | Ta < 60 °C | 10   | 90   | %RH  |

### 1.4 DC Electrical Characteristics

#### Module

GND = 0V, Ta = 25°C

| Item                     | Symbol          | Condition                       | Min.    | Typ. | Max.    | Unit |
|--------------------------|-----------------|---------------------------------|---------|------|---------|------|
| Power Supply Voltage     | VDD             | -                               | 3.0     | 3.3  | 3.6     | V    |
|                          | VGH             | -                               | 13      | 15   | 16      | V    |
|                          | VGL             | -                               | -10     | -10  | -7      | V    |
| Input H/L Level Voltage  | VIH             | -                               | 0.7VDD  | -    | VDD     | V    |
|                          | VIL             | -                               | 0       | -    | 0.3VDD  | V    |
| Output H/L Level Voltage | VOH             | -                               | VDD-0.4 | -    | VDD     | V    |
|                          | VOL             | -                               | 0       | -    | GND+0.4 | V    |
| Supply Current           | I <sub>DD</sub> | VDD = 3.3 V<br>Pattern=Photo *1 | -       | 25   | 40      | mA   |

Note1:Maximum current display

## 1.5 Optical Characteristics

### TFT LCD Module

VDD= 3.3 V, Ta=25°C



| Item  |        | Symbol      | Condition                                   | Min. | Typ. | Max. | unit  | -      |
|---|--------|-------------|---|------|------|------|-------|--------|
| Response time   | Tr+Tf  | 25          | -   | -    | 30   | -    | ms    | -      |
| Viewing angle   | Top    | $\theta Y+$ | CR $\geq$ 10                                | -    | 60   | -    | Deg.  | Note 4 |
|   | Bottom | $\theta Y-$ |   | -    | 60   | -    |       |        |
|   | Left   | $\theta X-$ |   | -    | 60   | -    |       |        |
|   | Right  | $\theta X+$ |   | -    | 60   | -    |       |        |
| Contrast ratio  |        | CR          |   | 500  | 600  | -    | -     | Note 3 |
| Color of CIE<br>Coordinate<br>( With B/L )                  | White  | X           | Ta = 25°C<br>$\theta X, \theta Y = 0^\circ$ | 0.24 | 0.29 | 0.34 | -     | Note1  |
|   |        | Y           |   | 0.29 | 0.34 | 0.39 |       |        |
|   | Red    | X           |   | 0.54 | 0.59 | 0.64 |       |        |
|   |        | Y           |   | 0.29 | 0.34 | 0.39 |       |        |
|   | Green  | X           |   | 0.28 | 0.33 | 0.38 |       |        |
|   |        | Y           |   | 0.57 | 0.62 | 0.67 |       |        |
|   | Blue   | X           |   | 0.10 | 0.15 | 0.20 |       |        |
|   |        | Y           |   | 0.06 | 0.11 | 0.16 |       |        |
| Average Brightness<br>Pattern=white display<br>(With LCD)*1 |        | IV          | IF= 20 mA                                   | 310  | 460  | -    | cd/m2 | Note1  |
| Uniformity<br>(With LCD)*2                                  |        | B           | IF= 20 mA                                   | 70   | -    | -    | %     | Note1  |

Note 1:

\*1 :  $B = B(\min) / B(\max) * 100\%$

\*2 : Measurement Condition for Optical Characteristics:

- a : Environment: 25 ±5 / 60±20%R.H , no wind , dark room below 10 Lux at typical lamp current and typical operating frequency.
- b : Measurement Distance: 500 ± 50 mm , ( $\theta = 0^\circ$ )
- c : Equipment: TOPCON BM-7 fast , (field 1°) , after 10 minutes operation.
- d : The uncertainty of the C.I.E coordinate measurement ±0.01 , Average Brightness ± 4%




To be measured at the center area of panel with a viewing cone of 1° by Topcon luminance meter BM-7, after 10 minutes operation (module)

Note2: Definition of response time:


The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of Amplitudes.

Refer to figure as below:

Normally White



Normally Black




Note3: Definition of contrast ratio:

Contrast ratio is calculated with the following formula

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note4: Definition of viewing angle:

Refer to figure as below:





## 1.6 Backlight Characteristics


### Maximum Ratings

| Item                              | Symbol | Conditions | Min. | Max. | Unit |
|-----------------------------------|--------|------------|------|------|------|
| LED Forward Current<br>(Each LED) | IF     | Ta =25     | -    | 30*1 | mA   |
| LED Reverse Voltage<br>(Each LED) | VR     | Ta =25     | -    | 5.0  | V    |
| Power Dissipation                 | PD     | Ta =25     | -    | 90*8 | mW   |

### Electrical / Optical Characteristics

| Item                                   | Symbol          | Conditions | Min. | Typ. | Max. | Unit              |
|--|-----------------|------------|------|------|------|-------------------|
| Forward Voltage                        | VF              | IF=20mA    | -    | 25.6 | -    | V                 |
| Average Brightness<br>(Without LCD )   | IV              |            | 6500 | 7800 | -    | cd/m <sup>2</sup> |
| CIE Color Coordinate<br>(Without LCD ) | X               |            | -    | 0.28 | -    | -                 |
|  | Y               |            | -    | 0.30 | -    |                   |
| Color                                  | White           |            |      |      |      |                   |
| LED Lifetime                           | 20000 Hrs at 25 |            |      |      |      |                   |

B/L Internal Circuit Diagram:




## 2. MODULE STRUCTURE

### 2.1 Counter Drawing

#### 2.1.1 LCM Mechanical Diagram

\* See Appendix

#### 2.1.2 Block Diagram





## 2.2 Interface Pin Description

| Pin No. | Symbol | Function                                     |
|---------|--------|--|
| 1       | K      | Power supply for LED Backlight cathode input |
| 2       | A      | Power supply for LED Backlight anode input   |
| 3       | GND    | Ground                                       |
| 4       | VDD    | Digital power                                |
| 5       | R0     | Red data bit 0                               |
| 6       | R1     | Red data bit 1                               |
| 7       | R2     | Red data bit 2                               |
| 8       | R3     | Red data bit 3                               |
| 9       | R4     | Red data bit 4                               |
| 10      | R5     | Red data bit 5                               |
| 11      | R6     | Red data bit 6                               |
| 12      | R7     | Red data bit 7                               |
| 13      | G0     | Green data bit 0                             |
| 14      | G1     | Green data bit 1                             |
| 15      | G2     | Green data bit 2                             |
| 16      | G3     | Green data bit 3                             |
| 17      | G4     | Green data bit 4                             |
| 18      | G5     | Green data bit 5                             |
| 19      | G6     | Green data bit 6                             |
| 20      | G7     | Green data bit 7                             |


| Pin No. | Symbol | Function  |
|---------|--------|---|
| 21      | B0     | Blue data bit 0   |
| 22      | B1     | Blue data bit 1   |
| 23      | B2     | Blue data bit 2   |
| 24      | B3     | Blue data bit 3   |
| 25      | B4     | Blue data bit 4   |
| 26      | B5     | Blue data bit 5   |
| 27      | B6     | Blue data bit 6   |
| 28      | B7     | Blue data bit 7   |
| 29      | GND    | Ground  |
| 30      | CLK    | Dot data clock  |
| 31      | DISP   | Display control / standby mode selection<br>"High" : Normal display |
| 32      | HSYNC  | Horizontal sync input   |
| 33      | VSYNC  | Vertical sync input   |
| 34      | DE     | Data input enable. Active High to enable the data input             |
| 35      | N.C    | Not Connect.  |
| 36      | GND    | Ground  |
| 37      | XR     | Not Connect.  |
| 38      | YB     | Not Connect.  |
| 39      | XL     | Not Connect.  |
| 40      | YT     | Not Connect.  |

## 2.3 Timing Characteristics

### 2.3.1 Clock and Data Input Timing



### 2.3.2 SYNC-DE MODE




| Item                         | Symbol | Min. | Typ. | Max. | Unit | Conditions  |
|------------------------------|--------|------|------|------|------|---|
| System operation timing      |        |      |      |      |      |   |
| VDD power source slew time   | TPOR   | -    | -    | 20   | ms   | From 0V to 99% VDD                                    |
| GRB pulse width              | tRSTW  | 10   | 50   | -    | us   | R=10Kohm, C=1uF                                       |
| Input/ Output timing         |        |      |      |      |      |   |
| CLK pulse duty               | Tcw    | 40   | 50   | 60   | %    |   |
| Hsync width                  | Thw    | 1    | -    | -    | DCLK |   |
| Hsync period                 | Th     | 55   | 60   | 65   | us   |   |
| Vsync setup time             | Tvst   | 12   | -    | -    | ns   |   |
| Vsync hold time              | Tvhd   | 12   | -    | -    | ns   |   |
| Hsync setup time             | Thst   | 12   | -    | -    | ns   |   |
| Hsync hold time              | Thhd   | 12   | -    | -    | ns   |   |
| Data setup time              | Tdsu   | 12   | -    | -    | ns   |   |
| Data hold time               | Tdhd   | 12   | -    | -    | ns   |   |
| SD output stable time        | Tst    | -    | -    | 12   | us   | Output settled within +20mV<br>Loading = 6.8k+28.2pF. |
| GD output rise and fall time | Tgst   | -    | -    | 6    | us   | Output settled (5%~95%),<br>Loading = 4.7k+29.8pF     |

### 2.3.3 Parallel RGB Input Timing Table

| Item           |                | Symbol | Min. | Typ. | Max. | Unit | Remark                |
|----------------|----------------|--------|------|------|------|------|-----------------------|
| DCLK Frequency |                | Fclk   | 9    | 12   | 15   | MHz  |                       |
| DCLK Period    |                | Tclk   | 67   | 83   | 111  | ns   |                       |
| HSYNC          | Period Time    | Th     | 485  | 525  | 532  | DCLK |                       |
|                | Display Period | Thdisp |      | 480  |      | DCLK |                       |
|                | Back Porch     | Thbp   | 3    | 43   | 50   | DCLK | By H_Blanking setting |
|                | Front Porch    | Thfp   | 2    | 2    | 2    | DCLK |                       |
|                | Pulse Width    | Thw    | 1    | 1    | 1    | DCLK |                       |
| VSYNC          | Period Time    | Tv     | 275  | 285  | 303  | H    |                       |
|                | Display Period | Tvdisp |      | 272  |      | H    |                       |
|                | Back Porch     | Tvbp   | 2    | 12   | 30   | H    | By V_Blanking setting |
|                | Front Porch    | Tvfp   | 1    | 1    | 1    | H    |                       |
|                | Pulse Width    | Tvw    | 1    | 1    | 1    | H    |                       |


### 2.3.4 SYNC-DE Mode Timing






### 3. QUALITY ASSURANCE SYSTEM

#### 3.1 Quality Assurance Flow Chart




| Item          | Customer  | Sales | R&D | Q.A | Manufacturing   | Product control | Purchase | Inventory control |
|---------------|---|-------|-----|-----|---|-----------------|----------|-------------------|
| Sales Service |  <pre> graph TD     Info[Info] --&gt; Claim[Claim]     Claim --&gt; Failure[Failure analysis]     Failure --&gt; Analysis[Analysis report]     Failure --&gt; Corrective[Corrective action]     Corrective --&gt; Tracking[Tracking]           </pre> |       |     |     |   |                 |          |                   |
| Q.A Activity  | 1. ISO 9001 Maintenance Activities<br>3. Equipment calibration<br>5. Standardization Management   |       |     |     | 2. Process improvement proposal<br>4. Education And Training Activities |                 |          |                   |

### 3.2 Inspection Specification


- ◆Scope : The document shall be applied to TFT-LCD Module for 3.5" ~10" (Ver.B01).
- ◆Inspection Standard : MIL-STD-105E Table Normal Inspection Single Sampling Level II.
- ◆Equipment : Gauge 、 MIL-STD 、 Powertip Tester 、 Sample
- ◆Defect Level : Major Defect AQL : 0.4 ; Minor Defect AQL : 1.5
- ◆OUT Going Defect Level : Sampling.
- ◆Standard of the product appearance test :

a. Manner of appearance test :

- (1). The test best be under 20W×2 fluorescent light , and distance of view must be at 30 cm.
- (2). The test direction is base on about around 45° of vertical line.



(3). Definition of area.



**A area : viewing area**



**B area : Outside of viewing area**


(4). Standard of inspection : (Unit : mm)



## ◆ Specification For TFT-LCD Module 3.5" ~10" :



(Ver.B01)

| NO   | Item  | Criterion  | Level |                   |                   |            |            |          |          |          |           |          |       |          |       |
|--|---|--|-------|-------------------|-------------------|------------|------------|----------|----------|----------|-----------|----------|-------|----------|-------|
| 01   | Product condition   | 1. 1 The part number is inconsistent with work order of production.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 1. 2 Mixed product types.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 1. 3 Assembled in inverse direction.   | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
| 02   | Quantity  | 2. 1 The quantity is inconsistent with work order of production.   | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
| 03   | Outline dimension   | 3. 1 Product dimension and structure must conform to structure diagram.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
| 04   | Electrical Testing  | 4. 1 Missing line character and icon.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 4. 2 No function or no display.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 4. 3 Display malfunction.  | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 4. 4 LCD viewing angle defect.   | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  |   | 4. 5 Current consumption exceeds product specifications.   | Major |                   |                   |            |            |          |          |          |           |          |       |          |       |
| 05   | Dot defect<br>(Bright dot 、<br>Dark dot)<br><br>On -display | <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>Item</th> <th>Acceptance (Q'ty)</th> </tr> </thead> <tbody> <tr> <td rowspan="4" style="text-align: center; vertical-align: middle;">Dot Defect</td> <td>Bright Dot</td> <td style="text-align: center;"><math>\leq 4</math></td> </tr> <tr> <td>Dark Dot</td> <td style="text-align: center;"><math>\leq 5</math></td> </tr> <tr> <td>Joint Dot</td> <td style="text-align: center;"><math>\leq 3</math></td> </tr> <tr> <td>Total</td> <td style="text-align: center;"><math>\leq 7</math></td> </tr> </tbody> </table> |       | Item              | Acceptance (Q'ty) | Dot Defect | Bright Dot | $\leq 4$ | Dark Dot | $\leq 5$ | Joint Dot | $\leq 3$ | Total | $\leq 7$ | Minor |
|  |   |  | Item  | Acceptance (Q'ty) |                   |            |            |          |          |          |           |          |       |          |       |
| Dot Defect   | Bright Dot  | $\leq 4$   |       |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  | Dark Dot  | $\leq 5$   |       |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  | Joint Dot   | $\leq 3$   |       |                   |                   |            |            |          |          |          |           |          |       |          |       |
|  | Total   | $\leq 7$   |       |                   |                   |            |            |          |          |          |           |          |       |          |       |
| 5. 1 Inspection pattern : full white , full black , Red , Green and blue screens.<br>5. 2 It is defined as dot defect if defect area $> 1/2$ dot.<br>5. 3 The distance between two dot defect $\geq 5$ mm. |   |  |       |                   |                   |            |            |          |          |          |           |          |       |          |       |

| NO                             | Item  | Criterion  | Level                          |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
|--------------------------------|---|--|--------------------------------|-------------------|--|--------|--------|------------------|--------|--|-------------------------|---|--------|-------------------------|---|---------------|---|--------------|-----------|-------------------|--|--------|--------|-----|---------------|--------|--------|---------------|----------------------|---|--------------|----------------------|---|-----|------------|---------------|--------------|--|---|-------|
| 06                             | <p>Black or white dot、scratch、contamination</p> <p>Round type</p>  <p><math>\Phi = (x + y) / 2</math></p> <p>Line type</p>  | <p>6.1 Round type ( Non-display or display) :</p> <table border="1"> <thead> <tr> <th rowspan="2">Dimension (diameter : <math>\Phi</math>)</th> <th colspan="2">Acceptance (Q'ty)</th> </tr> <tr> <th>A area</th> <th>B area</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.25</math></td> <td colspan="2">Ignore</td> </tr> <tr> <td><math>0.25 &lt; \Phi \leq 0.50</math></td> <td>5</td> <td rowspan="3">Ignore</td> </tr> <tr> <td><math>\Phi &gt; 0.50</math></td> <td>0</td> </tr> <tr> <td><b>Total</b></td> <td>5</td> </tr> </tbody> </table> <p>6.2 Line type( Non-display or display) :</p> <table border="1"> <thead> <tr> <th rowspan="2">Length (L)</th> <th rowspan="2">Width (W)</th> <th colspan="2">Acceptance (Q'ty)</th> </tr> <tr> <th>A area</th> <th>B area</th> </tr> </thead> <tbody> <tr> <td>---</td> <td><math>W \leq 0.03</math></td> <td>Ignore</td> <td rowspan="5">Ignore</td> </tr> <tr> <td><math>L \leq 10.0</math></td> <td><math>0.03 &lt; W \leq 0.05</math></td> <td>4</td> </tr> <tr> <td><math>L \leq 5.0</math></td> <td><math>0.05 &lt; W \leq 0.10</math></td> <td>2</td> </tr> <tr> <td>---</td> <td><math>W &gt; 0.10</math></td> <td>As round type</td> </tr> <tr> <td colspan="2"><b>Total</b></td> <td>5</td> </tr> </tbody> </table> | Dimension (diameter : $\Phi$ ) | Acceptance (Q'ty) |  | A area | B area | $\Phi \leq 0.25$ | Ignore |  | $0.25 < \Phi \leq 0.50$ | 5 | Ignore | $\Phi > 0.50$           | 0 | <b>Total</b>  | 5 | Length (L)   | Width (W) | Acceptance (Q'ty) |  | A area | B area | --- | $W \leq 0.03$ | Ignore | Ignore | $L \leq 10.0$ | $0.03 < W \leq 0.05$ | 4 | $L \leq 5.0$ | $0.05 < W \leq 0.10$ | 2 | --- | $W > 0.10$ | As round type | <b>Total</b> |  | 5 | Minor |
| Dimension (diameter : $\Phi$ ) | Acceptance (Q'ty)   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
|                                | A area  | B area   |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $\Phi \leq 0.25$               | Ignore  |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $0.25 < \Phi \leq 0.50$        | 5   | Ignore   |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $\Phi > 0.50$                  | 0   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| <b>Total</b>                   | 5   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| Length (L)                     | Width (W)   | Acceptance (Q'ty)  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
|                                |   | A area   | B area                         |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| ---                            | $W \leq 0.03$   | Ignore   | Ignore                         |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $L \leq 10.0$                  | $0.03 < W \leq 0.05$  | 4  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $L \leq 5.0$                   | $0.05 < W \leq 0.10$  | 2  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| ---                            | $W > 0.10$  | As round type  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| <b>Total</b>                   |   | 5  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| 07                             | Polarizer Bubble  | <table border="1"> <thead> <tr> <th rowspan="2">Dimension (diameter : <math>\Phi</math>)</th> <th colspan="2">Acceptance (Q'ty)</th> </tr> <tr> <th>A area</th> <th>B area</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.25</math></td> <td colspan="2">Ignore</td> </tr> <tr> <td><math>0.25 &lt; \Phi \leq 0.50</math></td> <td>4</td> <td rowspan="4">Ignore</td> </tr> <tr> <td><math>0.50 &lt; \Phi \leq 0.80</math></td> <td>1</td> </tr> <tr> <td><math>\Phi &gt; 0.80</math></td> <td>0</td> </tr> <tr> <td><b>Total</b></td> <td>5</td> </tr> </tbody> </table>  | Dimension (diameter : $\Phi$ ) | Acceptance (Q'ty) |  | A area | B area | $\Phi \leq 0.25$ | Ignore |  | $0.25 < \Phi \leq 0.50$ | 4 | Ignore | $0.50 < \Phi \leq 0.80$ | 1 | $\Phi > 0.80$ | 0 | <b>Total</b> | 5         | Minor             |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| Dimension (diameter : $\Phi$ ) | Acceptance (Q'ty)   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
|                                | A area  | B area   |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $\Phi \leq 0.25$               | Ignore  |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $0.25 < \Phi \leq 0.50$        | 4   | Ignore   |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $0.50 < \Phi \leq 0.80$        | 1   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| $\Phi > 0.80$                  | 0   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |
| <b>Total</b>                   | 5   |  |                                |                   |  |        |        |                  |        |  |                         |   |        |                         |   |               |   |              |           |                   |  |        |        |     |               |        |        |               |                      |   |              |                      |   |     |            |               |              |  |   |       |

| NO       | Item                                     | Criterion  | Level |   |   |   |          |                                |              |
|----------|--|--|-------|---|---|---|----------|--------------------------------|--------------|
| 08       | The crack of glass                       | <p><b>Symbols :</b></p> <p><b>X :</b> The length of crack<br/> <b>Z :</b> The thickness of crack<br/> <b>t :</b> The thickness of glass</p> <p><b>Y :</b> The width of crack.<br/> <b>W :</b> terminal length<br/> <b>a :</b> LCD side length</p>  | Minor |   |   |   |          |                                |              |
|          |  | <p>8.1 General glass chip :</p> <p>8.1.1 Chip on panel surface and crack between panels:</p>  <table border="1" data-bbox="544 1559 1347 1845"> <thead> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><math>\leq a</math></td> <td>Crack can't enter viewing area</td> <td><math>\leq 1/2 t</math></td> </tr> <tr> <td><math>\leq a</math></td> <td>Crack can't exceed the half of SP width.</td> <td><math>1/2 t &lt; Z \leq 2 t</math></td> </tr> </tbody> </table> |       | X | Y | Z | $\leq a$ | Crack can't enter viewing area | $\leq 1/2 t$ |
| X        | Y  | Z  |       |   |   |   |          |                                |              |
| $\leq a$ | Crack can't enter viewing area           | $\leq 1/2 t$   |       |   |   |   |          |                                |              |
| $\leq a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$   |       |   |   |   |          |                                |              |

| NO  | Item                                     | Criterion   | Level        |   |              |              |                                |                |              |  |                      |              |       |
|---|--|---|--------------|---|--------------|--------------|--------------------------------|----------------|--------------|--|----------------------|--------------|-------|
| 08  | The crack of glass                       | <p><b>Symbols :</b></p> <p><b>X :</b> The length of crack<br/> <b>Z :</b> The thickness of crack<br/> <b>t :</b> The thickness of glass</p> <p><b>Y :</b> The width of crack.<br/> <b>W :</b> terminal length<br/> <b>a :</b> LCD side length</p> <hr/> <p>8.1.2 Corner crack :</p>  <table border="1" data-bbox="525 759 1334 1048"> <thead> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><math>\leq 1/5 a</math></td> <td>Crack can't enter viewing area</td> <td><math>Z \leq 1/2 t</math></td> </tr> <tr> <td><math>\leq 1/5 a</math></td> <td>Crack can't exceed the half of SP width.</td> <td><math>1/2 t &lt; Z \leq 2 t</math></td> </tr> </tbody> </table> | X            | Y | Z            | $\leq 1/5 a$ | Crack can't enter viewing area | $Z \leq 1/2 t$ | $\leq 1/5 a$ | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$ |              |       |
|   |  | X   | Y            | Z |              |              |                                |                |              |  |                      |              |       |
| $\leq 1/5 a$  | Crack can't enter viewing area           | $Z \leq 1/2 t$  |              |   |              |              |                                |                |              |  |                      |              |       |
| $\leq 1/5 a$  | Crack can't exceed the half of SP width. | $1/2 t < Z \leq 2 t$  |              |   |              |              |                                |                |              |  |                      |              |       |
| <p>8.2 Protrusion over terminal :</p> <p>8.2.1 Chip on electrode pad :</p>  <table border="1" data-bbox="563 1680 1343 1850"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><b>Front</b></td> <td><math>\leq a</math></td> <td><math>\leq 1/2 W</math></td> <td><math>\leq t</math></td> </tr> <tr> <td><b>Back</b></td> <td><math>\leq a</math></td> <td><math>\leq W</math></td> <td><math>\leq 1/2 t</math></td> </tr> </tbody> </table> |  | X   | Y            | Z | <b>Front</b> | $\leq a$     | $\leq 1/2 W$                   | $\leq t$       | <b>Back</b>  | $\leq a$                                 | $\leq W$             | $\leq 1/2 t$ | Minor |
|   | X  | Y   | Z            |   |              |              |                                |                |              |  |                      |              |       |
| <b>Front</b>  | $\leq a$                                 | $\leq 1/2 W$  | $\leq t$     |   |              |              |                                |                |              |  |                      |              |       |
| <b>Back</b>   | $\leq a$                                 | $\leq W$  | $\leq 1/2 t$ |   |              |              |                                |                |              |  |                      |              |       |

| NO           | Item               | Criterion  | Level |   |   |   |              |          |          |   |   |   |
|--------------|--------------------|--|-------|---|---|---|--------------|----------|----------|---|---|---|
| 08           | The crack of glass | <p>Symbols :</p> <p>X : The length of crack                      Y : The width of crack.<br/>           Z : The thickness of crack                W : terminal length<br/>           t : The thickness of glass                 a : LCD side length</p>  | Minor |   |   |   |              |          |          |   |   |   |
|              |                    | <p>8.2.2 Non-conductive portion :</p>  <table border="1" data-bbox="630 963 1260 1120"> <thead> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><math>\leq 1/3 a</math></td> <td><math>\leq W</math></td> <td><math>\leq t</math></td> </tr> </tbody> </table> <p>⊙ If the chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.</p> <p>8.2.3 Glass remain :</p>  <table border="1" data-bbox="550 1736 1244 1881"> <thead> <tr> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><math>\leq a</math></td> <td><math>\leq 1/3 W</math></td> <td><math>\leq t</math></td> </tr> </tbody> </table> |       | X | Y | Z | $\leq 1/3 a$ | $\leq W$ | $\leq t$ | X | Y | Z |
| X            | Y                  | Z  |       |   |   |   |              |          |          |   |   |   |
| $\leq 1/3 a$ | $\leq W$           | $\leq t$   |       |   |   |   |              |          |          |   |   |   |
| X            | Y                  | Z  |       |   |   |   |              |          |          |   |   |   |
| $\leq a$     | $\leq 1/3 W$       | $\leq t$   |       |   |   |   |              |          |          |   |   |   |



## ◆Specification For TFT-LCD Module 3.5" ~10" :

(Ver.B01)

| NO | Item               | Criterion   | Level |
|----|--------------------|---|-------|
| 09 | Backlight elements | 9. 1 Backlight can't work normally.   | Major |
|    |                    | 9. 2 Backlight doesn't light or color is wrong.   | Major |
|    |                    | 9. 3 Illumination source flickers when lit.   | Major |
| 10 | General appearance | 10. 1 Pin type 、 quantity 、 dimension must match type in structure diagram.   | Major |
|    |                    | 10. 2 No short circuits in components on PCB or FPC .   | Major |
|    |                    | 10. 3 Parts on PCB or FPC must be the same as on the production characteristic chart .There should be no wrong parts , missing parts or excess parts. | Major |
|    |                    | 10. 4 Product packaging must the same as specified on packaging specification sheet.  | Minor |
|    |                    | 10. 5 The folding and peeled off in polarizer are not acceptable.   | Minor |
|    |                    | 10. 6 The PCB or FPC between B/L assembled distance(PCB or FPC ) is $\leq 1.5$ mm.  | Minor |

## 4. RELIABILITY TEST

### 4.1 Reliability Test Condition

(Ver.B01)

| NO.                 | TEST ITEM                                     | TEST CONDITION   |                     |                  |          |     |             |    |            |    |          |    |
|---------------------|---|--|---------------------|------------------|----------|-----|-------------|----|------------|----|----------|----|
| 1                   | High Temperature Storage Test                 | Keep in <b>+80 ±2</b> 96 hrs<br>Surrounding temperature, then storage at normal condition 4hrs.  |                     |                  |          |     |             |    |            |    |          |    |
| 2                   | Low Temperature Storage Test                  | Keep in <b>-30 ±2</b> 96 hrs<br>Surrounding temperature, then storage at normal condition 4hrs.  |                     |                  |          |     |             |    |            |    |          |    |
| 3                   | High Temperature / High Humidity Storage Test | Keep in <b>+60</b> / <b>90%</b> R.H duration for 96 hrs<br>Surrounding temperature, then storage at normal condition 4hrs.<br>(Excluding the polarizer)  |                     |                  |          |     |             |    |            |    |          |    |
| 4                   | Temperature Cycling Storage Test              | <div style="text-align: center;"> <math>-30 \rightarrow +25 \rightarrow +80 \rightarrow +25</math><br/>           (30mins) (5mins) (30mins) (5mins)<br/>           ←—————→<br/>           10 Cycle         </div> Surrounding temperature, then storage at normal condition 4hrs.  |                     |                  |          |     |             |    |            |    |          |    |
| 5                   | ESD Test                                      | <b>Air Discharge:</b><br>Apply <b>2 KV</b> with 5 times Discharge for each polarity +/-<br><b>Contact Discharge:</b><br>Apply <b>250 V</b> with 5 times discharge for each polarity +/-  |                     |                  |          |     |             |    |            |    |          |    |
|                     |   | 1. Temperature ambience : 15 35<br>2. Humidity relative : 30% 60%<br>3. Energy Storage Capacitance(Cs+Cd) : 150pF±10%<br>4. Discharge Resistance(Rd) : 330Ω±10%<br>5. Discharge, mode of operation :<br>Single Discharge (time between successive discharges at least 1 sec) (Tolerance if the output voltage indication : ±5%)  |                     |                  |          |     |             |    |            |    |          |    |
| 6                   | Vibration Test (Packaged)                     | 1. Sine wave <b>10 55</b> Hz frequency (1 min/sweep)<br>2. The amplitude of vibration : <b>1.5</b> mm<br>3. Each direction (X、 Y、 Z) duration for <b>2</b> Hrs   |                     |                  |          |     |             |    |            |    |          |    |
| 7                   | Drop Test (Packaged)                          | <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Packing Weight (Kg)</th> <th>Drop Height (cm)</th> </tr> </thead> <tbody> <tr> <td>0 ~ 45.4</td> <td>122</td> </tr> <tr> <td>45.4 ~ 90.8</td> <td>76</td> </tr> <tr> <td>90.8 ~ 454</td> <td>61</td> </tr> <tr> <td>Over 454</td> <td>46</td> </tr> </tbody> </table> <p>Drop Direction : 1 corner / 3 edges / 6 sides each 1time</p> | Packing Weight (Kg) | Drop Height (cm) | 0 ~ 45.4 | 122 | 45.4 ~ 90.8 | 76 | 90.8 ~ 454 | 61 | Over 454 | 46 |
| Packing Weight (Kg) | Drop Height (cm)                              |  |                     |                  |          |     |             |    |            |    |          |    |
| 0 ~ 45.4            | 122   |  |                     |                  |          |     |             |    |            |    |          |    |
| 45.4 ~ 90.8         | 76  |  |                     |                  |          |     |             |    |            |    |          |    |
| 90.8 ~ 454          | 61  |  |                     |                  |          |     |             |    |            |    |          |    |
| Over 454            | 46  |  |                     |                  |          |     |             |    |            |    |          |    |

## 5. PRECAUTION RELATING PRODUCT HANDLING

### 5.1 SAFETY

- 5.1.1 If the LCD panel breaks , be careful not to get the liquid crystal to touch your skin.
- 5.1.2 If the liquid crystal touches your skin or clothes , please wash it off immediately by using soap and water.

### 5.2 HANDLING

- 5.2.1 Avoid any strong mechanical shock which can break the glass.
- 5.2.2 Avoid static electricity which can damage the CMOS LSI—When working with the module , be sure to ground your body and any electrical equipment you may be using.
- 5.2.3 Do not remove the panel or frame from the module.
- 5.2.4 The polarizing plate of the display is very fragile. So , please handle it very carefully ,do not touch , push or rub the exposed polarizing with anything harder than an HB pencil lead (glass , tweezers , etc.)
- 5.2.5 Do not wipe the polarizing plate with a dry cloth , as it may easily scratch the surface of plate.
- 5.2.6 Do not touch the display area with bare hands , this will stain the display area.
- 5.2.7 Do not use ketonics solvent & aromatic solvent. Use with a soft cloth soaked with a cleaning naphtha solvent.
- 5.2.8 To control temperature and time of soldering is  $320\pm 10$  and 3-5 sec.
- 5.2.9 To avoid liquid (include organic solvent) stained on LCM .

### 5.3 STORAGE

- 5.3.1 Store the panel or module in a dark place where the temperature is  $25 \pm 5$  and the humidity is below 65% RH.
- 5.3.2 Do not place the module near organics solvents or corrosive gases.
- 5.3.3 Do not crush , shake , or jolt the module.


## 5.4 TERMS OF WARRANTY

### 5.4.1 Applicable warrant period


The period is within thirteen months since the date of shipping out under normal using and storage conditions.

### 5.4.2 Unaccepted responsibility

This product has been manufactured to your company's specification as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment , we cannot take responsibility if the product is used in nuclear power control equipment , aerospace equipment , fire and security systems or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required.




- NOTES:
- LCD TYPE: a-Si TFT
  - LCD DISPLAY: POSITIVE/TRANSMISSIVE
  - VIEW DIRECTION: 6 O'CLOCK
  - The tolerance unless classified  $\pm 0.2\text{mm}$
  - FPC suggested connector : 08 6262 040 340 846+(KYOCERA) or compatible
  - Component Area & Unbending Area



PIXEL Detail  
SCALE: 80/1

Detail A  
Scale: 2/1



|     |                      |         |            |
|-----|----------------------|---------|------------|
| 007 |                      |         |            |
| 006 |                      |         |            |
| 005 |                      |         |            |
| 004 |                      |         |            |
| 003 | Add Rear View        | Mandy   | 2015/05/20 |
| 002 | Modify Frame Drawing | Mandy   | 2014/06/04 |
| 001 | NEW DRAWING          | Mandy   | 2014/05/22 |
| REV | REV BY               | REVISER | DATE       |

TITLE:  
LCD Module Drawing

**US Micro Products**  
ENGINEERED DISPLAY SOLUTIONS

|        |             |           |         |  |  |  |  |  |  |           |     |          |          |           |
|--------|-------------|-----------|---------|--|--|--|--|--|--|-----------|-----|----------|----------|-----------|
| Design | Mandy Chang |           | Surface |  |  |  |  |  |  |           |     |          |          |           |
|        | Check       | Tina Chen |         |  |  |  |  |  |  | Unit      | MM  | Material |          |           |
|        |             | Approve   |         |  |  |  |  |  |  | Linda Lee |     | Scale    | 1:1      | Thickness |
|        |             |           |         |  |  |  |  |  |  | Page      | 1/1 |          | Quantity |           |

|     | Tolerance Length (mm) | Precision | Precision Level |
|-----|-----------------------|-----------|-----------------|
| 1   | ~ 4                   | -         | -               |
| 4   | ~ 16                  | -         | -               |
| 16  | ~ 63                  | -         | -               |
| 63  | ~ 250                 | -         | -               |
| 250 | ~ 1000                | -         | -               |