

27" High Brightness Touch Monitor



Features

- PCAP multi-touch screen
- Full flat surface fillet mirror design
- IP65 waterproof, dust-proof, vandal-proof
- LED Life Time: 50k hrs Typical
- Support camera / Light Sensor

- **Application:**

AFC / Non-cash equipment / Kiosk etc

Ordering Information

TBD	I P with 27" LCD, 1500nits(Light Sensor), 1920x1080 pixels, 178(H)x178(V), LED Backlight, 1000:1;
	VGA/DVI-D/HDMI/USB, PCAP Touch(10 points);

Specifications

LCD

Model Name	TBD
Screen Size	27"
Active Display Area(mm)	597.6(H)x336.15(V)
Pixel Pitch(mm)	0.31125(H)x0.31125(V)
Display Mode	Normally Black
Display Resolution(pixel)	1920x1080
Contrast Ratio	1000:1
Display Color	16.7M
Brightness	1500nits(Light Sensor)
Backlight	LED
Viewing Angles(CR=10)	178(H);178(V)
Response Time(Typ. Tr+Tf)	14ms

Optional

Touch Screen	PCAP Touch(10 points)
Light Sensor	Support
Tempered glass	Optional

I/O Interface

Signal Connector	VGA/DVI-D/HDMI
Power Input	DC 12V
Touch Controller(Optional)	USB

Mechanical

Dimension(VxHxT)mm	TBD
--------------------	-----

Environmental

Operating Temperature	-30~80℃ (non-condensation)
Storage Temperature	-30~80℃ (non-condensation)
Relative Humidity	5~90(%RH)